



Lina

55.. s




- Fire insert, open on one side
- 5545 - for tile size 22, H 45 cm
5551 - for tile size 25, H 51 cm
5557 - for tile size 28, H 57 cm
- Self-closing door, A1
- The lower panel for the secondary air is adjustable for an excellent glass wash
- Standard inner lining: fire clay, plain
- High-quality cast-iron dome, all parts are movable, adjustment from 0° to 90°
- Easy and fast adjustment of the construction height.
- Easily dismantles for transportation

Optional designs:



Optional comfort features:



Specifications

Rated thermal output	kW	7
Output range (depending on the fuel quantity)	kW	3,4 – 7,4
Efficiency	%	> 78
Insulation rear / side walls	mm	80 / 80
Ø Supply air line for external air connection	mm	125
Weight (depending on the equipment)	kg	200 – 220
Heat emission through glass	%	30
Convective heat	%	70

Data for chimney sweepers or responsible authority according to DIN EN 13384

(closed operation: A1 / open operation: A)

Triple value for NWL	Flue gas mass flow	g/s	A1	6,4
		g/s	A	---
	Flue gas temperature at the connector	°C	A1	260
		°C	A	---
	Required draught at the connector	mbar	A1	0,12
		mbar	A	---



Extension tank (4 storage rings)

Rated thermal output	kW	8
Efficiency	%	84,3



Hot air pipe coil extension

Rated thermal output	kW	9
Efficiency	%	88,7



Reheater box

Rated thermal output	kW	10
Efficiency	%	87,9



Hot air pipe coil extension

Rated thermal output	kW	10,5
Efficiency	%	89,8

Tested method DIN EN 13229

and in accordance with Regulation Art. 15a B-VG

Testing report nr.:

RRF - 29 10 2333



1. BImSchV. level 1




1. BImSchV. level 2




More informations:

Front view M 1:20



Side view M 1:20



Top view M 1:10

